STRAPPING & SUPPLIES

POLYESTER CORD STRAPPING

- Tougher, stronger, and safer than polypropylene strapping
- Will not scratch or mar delicate surfaces
- Available in Uniline bonded cord strapping
 and crosswoven cord strapping
- Uniline cord is manufactured by bonding fibres together and is easy to tie
- Crosswoven cord strapping has a
- cross weave added between the fibres
- Crosswoven strapping will not split or fray
 Used only in manual applications
- Polyester cord strapping offers
- excellent resistance to moisture
- Frequently used in outdoor applicationsHeavy-duty polyester sizes are frequently used in
- lumber applications, agricultural and boat industries

Strap Width'

1/4

3/8

1/2

5/8

3/4



Price/Each Bonded Wove







INDUSTRIAL WIRE BUCKLES

3/4", 1000/box Model No. PB908 Price/Each \$

DISPENSER Model No. PB753 Price/Each \$



1/2" POLYESTER STRAPPING KITS

Consists of the following components:

- 1- PB021 1/2" x 3900', 600-lb strength polyester strapping
- 1- PB753 dispenser
- 1- PA555 1/2" poly sealer

Model No. ded Woven

PB018

PB020

PR022

PB024

PB026

PB017

PB019

PR021

PB023

PB025

- 1- PC939 polypropylene and polyester tensioner
- 1- PA509 1/2" open seals, 2000/box



Strength Ibs.

300

450

600

725

900

Feet /Coil

7800

5250

3900

3000

2100

POLYESTER CORD HANDI-PAK

Woven

- Convenient self-dispensing coil for small uses or on job site packaging
- Contains 100 wire buckles



CORDEX	

Model No.	Туре	Strap Width"	Break Strength Ibs.	Feet /Ctn.	Price /Each
PB027	Bonded	1/2	600	750	
PB028	Woven	1/2	600	750	

POLYPROPYLENE **POLYPROPYLENE & STRAPPING SEALERS** POLYESTER STRAPPING • Heat treated steel construction **TENSIONERS** for superior strength and durability • Ideal for applications on flat surfaces Prevents strapping from Accepts strapping 3/8 -3/4" wide and up to 0.035" thick loosening during transit Long 18" handle requires less effort Superior design and performance · Use on open steel seals Premium copper bushings · Built-in strapping cutter For use with open seals or buckles **NO** Strap Width /Eac Model No. PC939 PA555 ≤ 0.027 1/2Price/Each \$ PA556 5/8 0.023 - 0.039 PF459 3/4 ≤ 0.027

ODUCTS

ES & P.

EQUIPMEN

TALWORKING

ENT MAIN

NCE HANI

1425